

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

JACKOBOARD® LIGNIN 20 mm



BEWI

The Norwegian EPD Foundation

Owner of the declaration:

BEWI ASA, Insulation and Construction

Product:

JACKOBOARD® LIGNIN 20 mm

Declared unit:

1 m²

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR.

NPCR 012:2022 Part B for Thermal insulation products

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-9801-9743

Registration number:

NEPD-9801-9743

Issue date:

22.04.2025

Valid to:

22.04.2030

EPD software:

LCAno EPD generator ID: 583547

General information

Product

JACKOBOARD® LIGNIN 20 mm

Program operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Declaration number:

NEPD-9801-9743

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR.
NPCR 012:2022 Part B for Thermal insulation products

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 m2 JACKOBOARD® LIGNIN 20 mm

Declared unit with option:

A1, A2, A3, A4, A5, C1, C2, C3, C4, D

Functional unit:

1 m2 JACKOBOARD® LIGNIN 20 mm thick

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Norway, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

BEWI ASA, Insulation and Construction
Contact person: Marc Storm Andersen
Phone: +45 72157902
e-mail: marc.andersen@bewi.com

Manufacturer:

BEWI Insulation Germany and Belgium

, Europe

Place of production:

JACKON Insulation GmbH
Ritzlebener Str.1
39619 Arendsee, Germany

Management system:

ISO 14001 og 9001 for all production sites

Organisation no:

925437948

Issue date:

22.04.2025

Valid to:

22.04.2030

Year of study:

2024

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804:2012+A2:2019 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway. NEPDT97

Developer of EPD: Mark Plate

Reviewer of company-specific input data and EPD: Martin Bendix

Approved:



Håkon Hauan, CEO EPD-Norge

Product

Product description:

JACKOBOARD® LIGNIN construction boards are made of extruded polymer rigid foam (JACKODUR® LIGNIN), with a coating of special mortar and glass fibre fabric on both sides. JACKODUR® LIGNIN is an extruded polymer foam (with lignin and rPS) produced on the basis EN 13164 and available in board shape with a density 36 kg/m³ in average (measured). Lignin is a biopolymer and is abundantly produced as a byproduct of the paper industry during the breakdown of cellulose. rPS is made from post-consumer waste. The calculated density of the construction board, including the coating, is 186 kg/m³. The surface weight of the 20 mm plate is 3,78 kg/m². The construction boards are supplied with smooth edges. Use of the product is subject to the relevant national regulations in the country of installation. In Germany, for example, this includes the building regulations of the individual federal states and the technical regulations derived from them.

Product specification

| Materials | kg | % |
|-----------------------------|-------|--------|
| Cement | 3,022 | 79,95 |
| Emissions and waste streams | 0,42 | 11,33 |
| Expansion gas | 0,021 | 0,56 |
| Fuels, fossil | 0,010 | 0,27 |
| Organic Polymer | 0,18 | 4,85 |
| Reinforcement | 0,11 | 3,016 |
| Total | 3,77 | 100,00 |

| Packaging | kg | % |
|-----------------------|------|--------|
| Packaging - Plastic | 0,01 | 1,99 |
| Packaging - Wood | 0,54 | 98,01 |
| Total incl. packaging | 4,33 | 100,00 |

Technical data:

| Name | Value | Unit | Norm |
|---|-------|---------------------|------------|
| Gross density of the core material (polymer foam) | > 30 | kg / m ³ | EN 1602 |
| Compressive strength | 0.3 | N/mm ² | EN 826 |
| Tensile strength | 0,3 | N/mm ² | EN 1607 |
| Reaction to fire | E | class | EN 13501-1 |
| Dimensional stability at 70°C and 90% relative humidity | < 5 | % | EN 1605 |
| Deformation under 40 kPa load and 70°C | < 5 | % | EN 1605 |

Market:

Europe

Reference service life, product

A reference service life (RSL) according to ISO 15686 cannot be declared. The durability of JACKOBOARD® LIGNIN is normally at least as long as the lifetime of the building in which it is used (more than 80 years).

Reference service life, building or construction works

LCA: Calculation rules

Declared unit:

1 m² JACKOBOARD® LIGNIN 20 mm

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

< 0,5%

Allocation:

The allocation is made in accordance with the provisions of EN 15804+A2. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

| Materials | Source | Data quality | Year |
|-----------------------------|---------------|-------------------|------|
| Cement | ecoinvent 3.6 | Database | 2019 |
| Emissions and waste streams | LCA.no | Database | 2024 |
| Expansion gas | ecoinvent 3.6 | Database | 2019 |
| Expansion gas | ecoinvent 3.6 | Database | 2020 |
| Fuels, fossil | ecoinvent 3.6 | Database | 2019 |
| Organic Polymer | Supplier | Supplier specific | 2022 |
| Packaging - Plastic | ecoinvent 3.6 | Database | 2019 |
| Packaging - Wood | ecoinvent 3.6 | Database | 2019 |
| Reinforcement | ecoinvent 3.6 | Database | 2019 |

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

| Product stage | | | Construction installation stage | | Use stage | | | | | | | End of life stage | | | | Beyond the system boundaries |
|---------------|-----------|---------------|---------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|------------------------------------|
| Raw materials | Transport | Manufacturing | Transport | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | X | MND | MND | MND | MND | MND | MND | MND | X | X | X | X | X |

System boundary:



Additional technical information:

www.jackon-insulation.com

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

| Transport from production place to user (A4) | Capacity utilisation (incl. return) % | Distance (km) | Fuel/Energy Consumption | Unit | Value (Liter/tonne) |
|---|---------------------------------------|---------------|-------------------------|-------|---------------------|
| Truck, 16-32 tonnes, EURO 6 (kgkm) | 36,7 % | 500 | 0,043 | l/tkm | 21,50 |
| Assembly (A5) | | | | | |
| | Unit | Value | | | |
| Waste, packaging, wood to average treatment - A5 (inkl transport) (kg) | kg | 0,54 | | | |
| Waste, packaging, plastic to average treatment - A5 (inkl transport) (kg) | kg | 0,011 | | | |
| De-construction demolition (C1) | | | | | |
| | Unit | Value | | | |
| Waste treatment, PS, Insulation, Germany (kg) | kg | 0,65 | | | |
| Demolition of insulated concrete, C1 (kg) | kg | 3,022 | | | |
| Waste processing (C3) | | | | | |
| | Unit | Value | | | |
| Waste, Polystyrene, incineration | kg | 0,59 | | | |
| Recycling of PS | kg | 0,065 | | | |
| Waste treatment of cement-based product after demolition, C3 (kg) | kg | 3,022 | | | |
| Disposal (C4) | | | | | |
| | Unit | Value | | | |
| Landfilling of ashes from incineration of PS | kg | 0,0017 | | | |
| Waste, inert waste, to landfill (kg) | kg | 3,022 | | | |
| Benefits and loads beyond the system boundaries (D) | | | | | |
| | Unit | Value | | | |
| substitution of electricity (MJ) | MJ | 0,72 | | | |
| Substitution of thermal energy (MJ) | MJ | 24,61 | | | |
| Substitution of expandable polystyrene, EPS, granulate (kg) | kg | 0,065 | | | |

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

| Environmental impact | | | | | | | | | | | |
|----------------------------------|------------------------|-----------|----------|----------|----------|----------|----------|----|----------|----------|-----------|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| GWP-total | kg CO ₂ -eq | 9,34E-02 | 3,32E-01 | 1,33E-01 | 3,54E-01 | 1,55E-02 | 1,21E-02 | 0 | 1,89E+00 | 2,49E-02 | -3,90E-01 |
| GWP-fossil | kg CO ₂ -eq | 1,13E+00 | 3,32E-01 | 1,33E-01 | 3,54E-01 | 1,55E-02 | 1,21E-02 | 0 | 1,89E+00 | 2,49E-02 | -3,83E-01 |
| GWP-biogenic | kg CO ₂ -eq | -1,04E+00 | 1,37E-04 | 5,95E-05 | 1,46E-04 | 7,10E-05 | 2,27E-06 | 0 | 3,16E-05 | 2,90E-05 | -1,75E-03 |
| GWP-luluc | kg CO ₂ -eq | 1,43E-03 | 1,18E-04 | 1,47E-05 | 1,26E-04 | 3,81E-06 | 9,53E-07 | 0 | 5,03E-06 | 6,11E-06 | -4,89E-03 |
| ODP | kg CFC11-eq | 7,85E-08 | 7,51E-08 | 1,75E-08 | 8,02E-08 | 2,38E-09 | 2,61E-09 | 0 | 1,78E-09 | 9,39E-09 | -1,04E-02 |
| AP | mol H ⁺ -eq | 6,33E-03 | 9,53E-04 | 1,62E-04 | 1,02E-03 | 1,18E-04 | 1,27E-04 | 0 | 2,42E-04 | 2,21E-04 | -1,98E-03 |
| EP-FreshWater | kg P -eq | 3,29E-05 | 2,65E-06 | 7,21E-07 | 2,83E-06 | 1,77E-07 | 4,40E-08 | 0 | 2,69E-07 | 2,82E-07 | -1,66E-05 |
| EP-Marine | kg N -eq | 1,38E-03 | 1,89E-04 | 3,76E-05 | 2,01E-04 | 5,13E-05 | 5,58E-05 | 0 | 1,13E-04 | 8,20E-05 | -5,07E-04 |
| EP-Terrestrial | mol N -eq | 1,56E-02 | 2,11E-03 | 4,12E-04 | 2,25E-03 | 5,43E-04 | 6,04E-04 | 0 | 1,21E-03 | 9,05E-04 | -5,46E-03 |
| POCP | kg NMVOC-eq | 4,79E-03 | 8,08E-04 | 1,42E-04 | 8,62E-04 | 1,40E-04 | 1,68E-04 | 0 | 2,93E-04 | 2,59E-04 | -1,87E-03 |
| ADP-minerals&metals ¹ | kg Sb-eq | 2,49E-05 | 9,16E-06 | 1,09E-06 | 9,77E-06 | 2,41E-07 | 1,86E-08 | 0 | 8,56E-08 | 2,24E-07 | -1,02E-06 |
| ADP-fossil ¹ | MJ | 1,24E+01 | 5,01E+00 | 2,01E+00 | 5,35E+00 | 1,75E-01 | 1,66E-01 | 0 | 1,82E-01 | 6,83E-01 | -7,41E+00 |
| WDP ¹ | m ³ | 1,39E+02 | 4,85E+00 | 6,44E-01 | 5,18E+00 | 2,77E-01 | 3,54E-02 | 0 | 7,61E+00 | 4,22E+00 | -1,15E+01 |

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

| Additional environmental impact indicators | | | | | | | | | | | | |
|--|-------------------|----------|----------|----------|----------|----------|----------|----|----------|----------|-----------|--|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D | |
| PM | Disease incidence | 6,43E-08 | 2,03E-08 | 9,65E-10 | 2,17E-08 | 1,45E-09 | 1,53E-08 | 0 | 1,22E-09 | 4,71E-09 | -7,88E-08 | |
| IRP ² | kgBq U235 -eq | 4,80E-02 | 2,19E-02 | 1,15E-03 | 2,34E-02 | 6,38E-04 | 7,25E-04 | 0 | 1,31E-03 | 3,12E-03 | -1,16E-02 | |
| ETP-fw ¹ | CTUe | 1,62E+01 | 3,72E+00 | 5,21E-01 | 3,97E+00 | 1,99E-01 | 9,10E-02 | 0 | 3,26E-01 | 3,74E-01 | -1,17E+01 | |
| HTP-c ¹ | CTUh | 8,60E-10 | 0,00E+00 | 4,00E-11 | 0,00E+00 | 2,20E-11 | 3,00E-12 | 0 | 8,20E-11 | 1,50E-11 | -2,35E-10 | |
| HTP-nc ¹ | CTUh | 2,38E-08 | 4,06E-09 | 6,83E-10 | 4,33E-09 | 1,05E-09 | 8,50E-11 | 0 | 3,18E-09 | 2,72E-10 | -1,07E-08 | |
| SQP ¹ | dimensionless | 1,04E+02 | 3,51E+00 | 2,45E-01 | 3,74E+00 | 1,02E-01 | 2,02E-02 | 0 | 5,15E-02 | 2,63E+00 | -1,36E+01 | |

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

| Resource use | | | | | | | | | | | | |
|--------------|----------------|----------|----------|----------|----------|----------|----------|----|-----------|----------|-----------|--|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D | |
| PERE | MJ | 7,26E+00 | 7,18E-02 | 1,11E+00 | 7,66E-02 | 3,61E-03 | 9,07E-04 | 0 | 3,76E-02 | 2,45E-02 | -1,16E+01 | |
| PERM | MJ | 9,93E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0 | -2,41E+00 | 0,00E+00 | 0,00E+00 | |
| PERT | MJ | 1,72E+01 | 7,18E-02 | 1,11E+00 | 7,66E-02 | 3,61E-03 | 9,07E-04 | 0 | -2,37E+00 | 2,45E-02 | -1,16E+01 | |
| PENRE | MJ | 1,20E+01 | 5,01E+00 | 2,01E+00 | 5,35E+00 | 1,75E-01 | 1,66E-01 | 0 | 1,82E-01 | 6,83E-01 | -7,41E+00 | |
| PENRM | MJ | 4,67E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0 | 0,00E+00 | 0,00E+00 | 0,00E+00 | |
| PENRT | MJ | 1,24E+01 | 5,01E+00 | 2,01E+00 | 5,35E+00 | 1,75E-01 | 1,66E-01 | 0 | 1,82E-01 | 6,83E-01 | -7,41E+00 | |
| SM | kg | 4,28E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0 | 0,00E+00 | 0,00E+00 | 0,00E+00 | |
| RSF | MJ | 2,83E-02 | 2,57E-03 | 5,47E-04 | 2,74E-03 | 1,05E-04 | 0,00E+00 | 0 | 9,28E-05 | 5,08E-04 | -1,38E-03 | |
| NRSF | MJ | 4,18E-03 | 9,18E-03 | 4,71E-04 | 9,80E-03 | 1,18E-03 | 0,00E+00 | 0 | 0,00E+00 | 1,29E-03 | -7,45E-01 | |
| FW | m ³ | 8,06E-03 | 5,36E-04 | 1,00E-03 | 5,72E-04 | 1,27E-04 | 8,57E-06 | 0 | 4,41E-04 | 8,40E-04 | -1,16E-02 | |

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

*Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

| End of life - Waste | | | | | | | | | | | | |
|---|------|----|----------|----------|----------|----------|----------|----------|----|----------|----------|-----------|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D | |
|  | HWD | kg | 5,53E-03 | 2,59E-04 | 1,97E-04 | 2,76E-04 | 0,00E+00 | 4,90E-06 | 0 | 6,66E-06 | 1,53E-03 | -1,41E-04 |
|  | NHWD | kg | 1,37E-01 | 2,44E-01 | 1,02E-02 | 2,60E-01 | 5,53E-01 | 1,97E-04 | 0 | 2,10E-04 | 3,02E+00 | -4,46E-02 |
|  | RWD | kg | 4,30E-05 | 3,41E-05 | 1,52E-06 | 3,64E-05 | 0,00E+00 | 1,16E-06 | 0 | 7,05E-07 | 5,05E-09 | -9,99E-06 |

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

| End of life - Output flow | | | | | | | | | | | | |
|---|------|----|----------|----------|----------|----------|----------|----|----------|----------|----------|--|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D | |
|  | CRU | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0 | 0,00E+00 | 0,00E+00 | 0,00E+00 | |
|  | MFR | kg | 0,00E+00 | 0,00E+00 | 1,08E-02 | 0,00E+00 | 5,63E-03 | 0 | 3,09E+00 | 0,00E+00 | 0,00E+00 | |
|  | MER | kg | 0,00E+00 | 0,00E+00 | 2,52E-03 | 0,00E+00 | 5,42E-01 | 0 | 5,92E-01 | 0,00E+00 | 0,00E+00 | |
|  | EEE | MJ | 0,00E+00 | 0,00E+00 | 3,76E-03 | 0,00E+00 | 3,77E-01 | 0 | 1,04E+00 | 0,00E+00 | 0,00E+00 | |
|  | EET | MJ | 0,00E+00 | 0,00E+00 | 5,69E-02 | 0,00E+00 | 5,70E+00 | 0 | 1,58E+01 | 0,00E+00 | 0,00E+00 | |

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3} = 0,009$

*INA Indicator Not Assessed

| Biogenic Carbon Content | | |
|---|------|---------------------|
| Indicator | Unit | At the factory gate |
| Biogenic carbon content in product | kg C | 6,06E-02 |
| Biogenic carbon content in accompanying packaging | kg C | 2,24E-01 |

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

| Electricity mix | Source | Amount | Unit |
|---|---------------|--------|---------------------------|
| Electricity, with Guarantee of origin, 01.01.2025 - 31.12.2025 - BEWI Arendsee, Germany (kWh) | ecoinvent 3.6 | 29,24 | g CO ₂ -eq/kWh |

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

JACKOBOARD® LIGNIN can be used indoor however they are generally not exposed to the indoor air but covered by a finishing element or system. The VOC emission testing meets the requirements of the AgBB/DIBt method. The tested products all comply with the requirements of DIBt and AgBB for the use in the indoor environment. The tested products also all achieved the A+ rating of the French VOC labelling scheme.

Additional Environmental Information

| Additional environmental impact indicators required in NPCR Part A for construction products | | | | | | | | | | | |
|--|------------------------|----------|----------|----------|----------|----------|----------|----|----------|----------|-----------|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| GWPIOBC | kg CO ₂ -eq | 5,61E-01 | 3,32E-01 | 1,30E-01 | 3,54E-01 | 1,55E-02 | 1,21E-02 | 0 | 1,89E+00 | 2,49E-02 | -3,87E-01 |

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21

Vold et. al., (2022) EPD generator for NPCR 012 Thermal insulation, Background information for EPD generator application and LCA data, LCA.no report number: 07.22.

NPCR Part A: Construction products and services. Ver. 2.0. April 2021, EPD-Norge.

NPCR 012 Part B for Part B for Thermal insulation products, Ver. 2.0, 31.03.2022, EPD Norway.

| | | |
|---|--|--|
|  <small>Global program operator</small> | Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway | Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no |
|  | Owner of the declaration: BEWI ASA, Insulation and Construction Hammarvikringen 64, HAMAR 7263, Norway | Phone: +45 72157902 e-mail: marc.andersen@bewi.com web: https://bewi.com |
|  | Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | ECO Platform ECO Portal | web: www.eco-platform.org web: ECO Portal |