

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form: Mixture
 Trade name: JACKODUR® perimeter adhesive foam
 Vaporizer: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

Intended for general public

Main use category: Consumer use, Professional use

Use of the substance/mixture: Polyurethane

1.2.2 Uses advised against

No additional information available

1.3 Details of the supplier of the safety data sheet:

Lieferant des Sicherheitsdatenblattes

JACKON Insulation GmbH

Ritzlebener Straße 1

D-39619 Arendsee

T +49 (0) 39036 / 960-0

F +49 (0) 39036 / 960-290

E info@jackodur.com

1.4 Emergency telephone number:

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons / Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
 Acute toxicity (inhalation:dust,mist) Category 4 H332
 Skin corrosion/irritation, Category 2 H315
 Serious eye damage/eye irritation, Category 2 H319
 Respiratory sensitisation, Category 1 H334

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: **2.0 issued on 31.01.2023**

Replaced version: **1.0 from 23.02.2017**

Region: **EU**

Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity – Repeated exposure, Category 2	H373
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP):

Danger

Contains:

polymethylene polyphenyl isocyanate

Hazard statements (CLP):

H222 - Extremely flammable aerosol.
 H229 - Pressurised container: May burst if heated.
 H315 - Causes skin irritation.
 H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H332 - Harmful if inhaled.
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 - May cause respiratory irritation.
 H351 - Suspected of causing cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP):

P101 - If medical advice is needed, have product container or label at hand.
 P102 - Keep out of reach of children.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P308+P313 - IF exposed or concerned: Get medical advice/attention.
 P405 - Store locked up.
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: **2.0 issued on 31.01.2023**

Replaced version: **1.0 from 23.02.2017**

Region: **EU**

Extra phrases:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

The product does not meet the PBT and vPvB classification criteria

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component

polymethylene polyphenyl isocyanate (9016-87-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
dimethyl ether (115-10-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
polymethylene polyphenyl isocyanate	CAS-No.: 9016-87-9	≥ 25 – < 50	Carc. 2, H351 Resp. Sens. 1, H334 Skin Sens. 1, H317 Acute Tox. 4 (Inhalativ), H332 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
reaction products of phosphoryl trichloride and 2-methyloxirane	CAS-Nr.: 1244733-77-4 EG-Nr.: 807-935-0 REACH-Nr.: 01-2119486772-26	≥ 10 – < 25	Acute Tox. 4 (Oral), H302 Aquatic Chronic 3, H412
dimethyl ether (Propellant gas (Aerosol))	CAS-Nr.: 115-10-6 EG-Nr.: 204-065-8 EG Index-Nr.: 603-019-00-8 REACH-Nr.: 01-2119472128-37	≥ 10 – < 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
isobutane (Propellant gas (Aerosol))	CAS-Nr.: 75-28-5 EG-Nr.: 200-857-2 EG Index-Nr.: 601-004-00-0 REACH-Nr.: 01-2119485395-27	≥ 5 – < 10	Flam. Gas 1A, H220 Press. Gas (Liq.), H28
propane (Propellant gas (Aerosol))	CAS-Nr.: 74-98-6 EG-Nr.: 200-827-9 EG Index-Nr.: 601-003-00-5 REACH-Nr.: 01-2119486944-21RE- ACH-Nr.: 01-2119486944-21	≥ 1 – < 5	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Comments: polymethylene polyphenyl isocyanate, contains > 0.1% MDI isomers

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general:	IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation:	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact:	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion:	Call a poison center or a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation:	May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/effects after skin contact:	Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact:	Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media:	None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard:	Extremely flammable aerosol.
Explosion hazard:	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire:	Toxic fumes may be released.

5.3 Advice for firefighters

Protection during firefighting:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
---------------------------------	--

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Emergency procedures: Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2 For emergency responders

Protective equipment: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2 Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Leave the product to solidify. Mechanically recover the product. Carefully collect the spill/leftovers. Notify authorities if product enters sewers or public waters. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

Other information: Dispose of materials or solid residues at an authorized site.

6.4 Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Incompatible products:	Heat sources. Ignition sources. Strong bases. Strong acids.
Packaging materials:	Aerosol.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

dimethyl ether (115-10-6)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Dimethylether
IOEL TWA	1920 mg/m ³
IOEL TWA [ppm]	1000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

Belgium - Occupational Exposure Limits

Local name	Oxyde de diméthyle # Dimethylether
OEL TWA	1920 mg/m ³
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

propane (74-98-6)

Belgium - Occupational Exposure Limits

Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020

isobutane (75-28-5)

Belgium - Occupational Exposure Limits

Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan
OEL STEL	2370 mg/m ³
OEL STEL [ppm]	980 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3 Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5 Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls::

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment:



according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing.

Hand protection: Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection: [In case of inadequate ventilation] wear respiratory protection.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Variable
Appearance:	Aerosol
Odour:	characteristic
Odour threshold:	Not available
Melting point:	Not available
Freezing point:	Not available
Boiling point:	Not available
Flammability:	Extremely flammable aerosol.
Explosive properties:	Pressurised container: May burst if heated.
Explosive limits:	Not available
Lower explosion limit:	Not available
Upper explosion limit:	Not available
Flash point:	Not applicable
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
pH:	Not available
Viscosity, kinematic:	Not available
Solubility:	Not available
Partition coefficient n-octanol/water (Log Kow):	Not available
Vapour pressure:	Not available
Vapour pressure at 50 °C:	Not available
Density:	993 kg/m ³ (20°C)
Relative density:	0,993 (20°C)
Relative vapour density at 20 °C:	Not available
Particle characteristics:	Not applicable

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients: 20

9.2.2. Other safety characteristics

VOC content: < 21 % (208.53 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral):	Not classified
Acute toxicity (dermal):	Not classified
Acute toxicity (inhalation):	Harmful if inhaled.

JACKODUR® perimeter adhesive foam

ATE CLP (dust,mist)	3,548 mg/l/4h
---------------------	---------------

dimethyl ether (115-10-6)

LC50 Inhalation - Rat [ppm]	164000 ppm (4 h, Rat, Male, Experimental value, Inhalation (gases), 14 day(s))
-----------------------------	--

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

propane (74-98-6)

LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
-----------------------------	---

isobutane (75-28-5)

LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))
-----------------------------	---

polymethylene polyphenyl isocyanate (9016-87-9)

LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
---------------	---

LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
--------------------	---

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

LD50 oral rat	632 mg/kg
---------------	-----------

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

LC50 Inhalation - Rat	> 7 mg/l/4h
-----------------------	-------------

Skin corrosion/irritation:	Causes skin irritation.
----------------------------	-------------------------

Serious eye damage/irritation:	Causes serious eye irritation.
--------------------------------	--------------------------------

Respiratory or skin sensitisation:	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
------------------------------------	---

Germ cell mutagenicity:	Not classified.
-------------------------	-----------------

Carcinogenicity:	Suspected of causing cancer.
------------------	------------------------------

polymethylene polyphenyl isocyanate (9016-87-9)

IARC-Gruppe	3 - Not classifiable
-------------	----------------------

Reproductive toxicity:	Not classified.
------------------------	-----------------

STOT-single exposure:	May cause respiratory irritation.
-----------------------	-----------------------------------

polymethylene polyphenyl isocyanate (9016-87-9)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure:	May cause damage to organs through prolonged or repeated exposure.
-------------------------	--

polymethylene polyphenyl isocyanate (9016-87-9)

STOT-repeated exposure:	May cause damage to organs through prolonged or repeated exposure (if inhaled).
-------------------------	---

Aspiration hazard:	Not classified
--------------------	----------------

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

JACKODUR® perimeter adhesive foam

Vaporizer

Aerosol

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general:

The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute):

Nicht eingestuft.

Hazardous to the aquatic environment, long-term (chronic):

Not classified

Not rapidly degradable

dimethyl ether (115-10-6)

LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with <i>Poecilia reticulata</i> , 96 h, <i>Poecilia reticulata</i> , Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with <i>Daphnia magna</i> , 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, Lethal)
EC50 96h - Algae [1]	154,9 mg/l (ECOSAR v1.00, Algae, QSAR, Estimated value)

propane (74-98-6)

LC50 - Fish [1]	49,9 mg/l (96 h, Pisces, Fresh water, QSAR, Estimated value)
EC50 96h - Algae [1]	11,89 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

isobutane (75-28-5)

LC50 - Fish [1]	27,98 mg/l (ECOSAR v1.00, 96 h, Pisces, Fresh water, QSAR)
EC50 96h - Algae [1]	8,57 mg/l (ECOSAR v1.00, Algae, Fresh water, QSAR)

polymethylene polyphenyl isocyanate (9016-87-9)

LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
------------------------------------	--------------------------------------

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

LC50 - Fish [1]	51 mg/l Pimephalis promelas
EC50 - Crustacea [1]	131 mg/l Daphnia magna
EC50 72h - Algae [1]	82 mg/l Pseudokirchnerella subcapitata
NOEC chronic crustacea	32 mg/l
NOEC chronic algae	13 mg/l

12.2. Persistence and degradability

dimethyl ether (115-10-6)

Persistence and degradability not readily degradable in water.

propane (74-98-6)

Persistence and degradability Readily biodegradable in water.

isobutane (75-28-5)

Persistence and degradability Readily biodegradable in water.

polymethylene polyphenyl isocyanate (9016-87-9)

Persistence and degradability not readily degradable in water.

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Persistence and degradability	not readily degradable in water.
Biodegradation	14 % OECD 301E

12.3. Bioaccumulative potential

dimethyl ether (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	0,1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

propane (74-98-6)

Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

isobutane (75-28-5)

Partition coefficient n-octanol/water (Log Pow)	1,09 – 2,8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

polymethylene polyphenyl isocyanate (9016-87-9)

BCF - Fish [1]	1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	10,46 (Calculated, KOWWIN)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

BCF - Fish [1]	0,8 – 14
Partition coefficient n-octanol/water (Log Pow)	2,68

12.4. Mobility in soil

polymethylene polyphenyl isocyanate (9016-87-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9,078 – 10,597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Product adsorbs onto the soil.

reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2,24
--	------

12.5. Results of PBT and vPvB assessment

JACKODUR® perimeter adhesive foam

The product does not meet the PBT and vPvB classification criteria

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations:	Do not discharge into drains or the environment.
Additional information:	Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.
Ecology - waste materials:	Avoid release to the environment.
European List of Waste (LoW) code:	08 05 01* - waste isocyanates 16 05 04* - gases in pressure containers (including halons) containing dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

No supplementary information available

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

14.6. Special precautions for user

Overland transport

Classification code (ADR):	5F
Special provisions (ADR):	190, 327, 344, 625
Limited quantities (ADR):	1L
Excepted quantities (ADR):	E0
Packing instructions (ADR):	P207, LP200
Special packing provisions (ADR):	PP87, RR6, L2
Mixed packing provisions (ADR):	MP9
Transport category (ADR):	2
Special provisions for carriage - Packages (ADR):	V14
Special provisions for carriage - Loading, unloading and handling (ADR):	CV9, CV12
Special provisions for carriage - Operation (ADR):	S2
Tunnel restriction code (ADR):	D

Transport by sea

Special provisions (IMDG):	63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG):	P207, LP200
Special packing provisions (IMDG):	PP87, L2
EmS-No. (Fire):	F-D
EmS-No. (Spillage):	S-U
Stowage category (IMDG):	None
Stowage and handling (IMDG):	SW1, SW22
Segregation (IMDG):	SG69

Air transport

PCA Excepted quantities (IATA):	E0
PCA Limited quantities (IATA):	Y203
PCA limited quantity max net quantity (IATA):	30kgG
PCA packing instructions (IATA):	203
PCA max net quantity (IATA):	75kg
CAO packing instructions (IATA):	203
CAO max net quantity (IATA):	150kg
Special provisions (IATA):	A145, A167, A802
ERG code (IATA):	10L

Inland waterway transport

Classification code (ADN):	5F
Special provisions (ADN):	190, 327, 344, 625
Limited quantities (ADN):	1 L
Excepted quantities (ADN):	E0
Equipment required (ADN):	PP, EX, A
Ventilation (ADN):	VE01, VE04
Number of blue cones/lights (ADN):	1

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

Rail transport

Classification code (RID):	5F
Special provisions (RID):	190, 327, 344, 625
Limited quantities (RID):	1L
Excepted quantities (RID):	E0
Packing instructions (RID):	P207, LP200
Special packing provisions (RID):	PP87, RR6, L2
Mixed packing provisions (RID):	MP9
Beförderungskategorie (RID):	2
Transport category (RID):	W14
Special provisions for carriage - Loading, unloading and handling (RID):	CW9, CW12
Colis express (express parcels) (RID):	CE2
Hazard identification number (RID):	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on	Entry title or description
3(a)	JACKODUR® perimeter adhesive foam	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(b)	JACKODUR® perimeter adhesive foam ; polymethylene polyphenyl isocyanate ; reaction products of phosphoryl trichloride and 2-methyloxirane	Stoffe oder Gemische, die den Kriterien einer der nachstehenden Gefahrenstufen oder -kategorien gemäß Anhang I der Verordnung (EG) Nr. 1272/2008 entsprechen: Gefahrenklassen 3.1 bis 3.6, 3.7 Beeinträchtigung der Sexualfunktion und Fruchtbarkeit sowie der Entwicklung, 3.8 ausgenommen narkotisierende Wirkungen, 3.9 und 3.10
40.	dimethyl ether ; propane ; isobutane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

EU-Beschränkungsliste (REACH-Anhang XVII)

Referenzcode	Anwendbar auf	Titel oder Beschreibung des Eintrags
56.	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI)
56(a)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl diisocyanate
56(b)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,4'-Methylenediphenyl diisocyanate
56(c)	polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) isomers: 2,2'-Methylenediphenyl diisocyanate
74.	polymethylene polyphenyl isocyanate	Diisocyanates, $O = C=N-R-N = C=O$, with R an aliphatic or aromatic hydrocarbon unit of unspecified length

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC-Gehalt: < 21 % (208.53 g/l)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		
2.2		Modified	
3	Composition/information on ingredients	Modified	

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BKF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EG-Nr.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

Abbreviations and acronyms:

LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDB	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-Nr.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:- dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Trade name: **JACKODUR® perimeter adhesive foam**

Current version: 2.0 issued on 31.01.2023

Replaced version: 1.0 from 23.02.2017

Region: EU

Full text of H- and EUH-statements:

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Aerosol 1	H222;H229	On basis of test data
Acute Tox. 4 (Inhalation: dust, mist)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

Safety Data Sheet (SDS), EU-20212

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.